


APPLICATION

PART NO	HEIGHT "H"		OUTSIDE DIA.		INSIDE DIA.	
	MM	INCH	MM	INCH	MM	INCH
LS-LED-V06-2	2.2	0.087	5.6	0.220	3.8	0.150
LS-LED-V06-2.5	2.6	0.102	5.9	0.232	3.8	0.150
LS-LED-V06-3	3.2	0.126	5.6	0.220	3.8	0.150
LS-LED-V06-4	4.1	0.161	5.6	0.220	3.8	0.150
LS-LED-V06-7.5	7.5	0.295	5.6	0.220	3.8	0.150
LS-LED-V06-8.8	8.8	0.346	5.6	0.220	3.8	0.150
LS-LED-V06-9.5	9.5	0.374	5.0	0.197	3.5	0.138
LS-LED-V06-9.8	9.8	0.386	5.6	0.220	3.8	0.150
LS-LED-V06-11	11.0	0.433	5.0	0.197	3.5	0.138
LS-LED-V06-12	12.0	0.472	5.8	0.228	3.9	0.154
LS-LED-V06-14	14.0	0.551	5.0	0.197	3.7	0.146
LS-LED-V06-15	15.0	0.591	5.6	0.220	3.9	0.154
LS-LED-V06-18.5	18.5	0.728	5.7	0.224	3.9	0.154
LS-LED-V06-21	21.0	0.827	5.1	0.201	3.8	0.150
LS-LED-V06-24	24.0	0.945	5.8	0.228	3.9	0.154
LS-LED-V06-37	37.5	1.476	5.8	0.228	3.9	0.154

NOTES:

- FOR 5MM(T1 3/4) LED
- MATERIAL FLAMMABILITY RATING: UL94V-2
- CUSTOM MATERIAL AVAILABLE
- CUSTOM COLOR AVAILABLE

DESCRIPTION NYLON LED SPACER			 THIRD ANGLE PROJECTION		Vaisis www.vaisis.com	
DWG DIMENSIONS UNLESS NOTED MM [INCH]	DWG. No. DW-LS-LED-V06	PART No. SEE TABLE	DWN YW	DATE 4/13/2011	CHKD YW	DATE 4/13/2011
TOLERANCES UNLESS NOTED .X=±0.20 [0.008] .XX=±0.10 [0.004] FRAC=±1/64 ANG=1°	MATERIAL NYLON 66	COLOR NATURAL	SCALE 4:1	SHEET SIZE A	SHEET No. 1 OF 1	

A	INITIAL RELEASE	4/13/2011	GC
REV.	DESCRIPTION	DATE	APPROVED