



APPLICATION

NOTES:

- FOR 5MM(T 1 3/4) LED
- MATERIAL FLAMMABILITY RATING: UL94V-2
- CUSTOM MATERIAL AVAILABLE
- CUSTOM COLOR AVAILABLE

| PART NO | HEIGHT "H" | | OUTSIDE DIA. | | INSIDE DIA. | |
|------------------|------------|-------|--------------|-------|-------------|-------|
| | MM | INCH | MM | INCH | MM | INCH |
| LS-LED-V06S-2A | 2.0 | 0.079 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-2.5A | 2.5 | 0.098 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-3A | 3.0 | 0.118 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-3.5 | 3.5 | 0.138 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-3.6 | 3.6 | 0.142 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-4C | 4.0 | 0.157 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-4.5A | 4.5 | 0.177 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-4.5 | 4.5 | 0.177 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-5A | 5.0 | 0.197 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-5 | 5.0 | 0.197 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-5.5 | 5.5 | 0.217 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-6A | 6.0 | 0.236 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-6 | 6.0 | 0.236 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-6S | 6.0 | 0.236 | 5.7 | 0.224 | 3.8 | 0.150 |
| LS-LED-V06S-6.5A | 6.5 | 0.256 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-6.8 | 6.8 | 0.268 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-7 | 7.0 | 0.276 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-7.5A | 7.5 | 0.295 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-7.8 | 7.8 | 0.307 | 5.8 | 0.228 | 3.9 | 0.154 |
| LS-LED-V06S-7.9 | 7.9 | 0.311 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-8 | 8.0 | 0.315 | 5.6 | 0.220 | 3.8 | 0.150 |
| LS-LED-V06S-8.5A | 8.5 | 0.335 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-9 | 9.0 | 0.354 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-9.5 | 9.5 | 0.374 | 5.0 | 0.197 | 3.5 | 0.138 |
| LS-LED-V06S-10 | 10.0 | 0.394 | 5.0 | 0.197 | 3.5 | 0.138 |
| LS-LED-V06S-10A | 10.0 | 0.394 | 5.9 | 0.232 | 3.9 | 0.154 |
| LS-LED-V06S-10.6 | 10.7 | 0.421 | 5.1 | 0.201 | 3.6 | 0.142 |
| LS-LED-V06S-11A | 11.0 | 0.433 | 5.8 | 0.228 | 3.8 | 0.150 |
| LS-LED-V06S-12A | 12.0 | 0.472 | 5.0 | 0.197 | 3.2 | 0.126 |
| LS-LED-V06S-13 | 13.0 | 0.512 | 5.0 | 0.197 | 3.6 | 0.142 |
| LS-LED-V06S-13.8 | 13.8 | 0.543 | 5.0 | 0.197 | 3.7 | 0.146 |
| LS-LED-V06S-14A | 14.0 | 0.551 | 5.0 | 0.197 | 3.7 | 0.146 |
| LS-LED-V06S-15A | 15.2 | 0.598 | 5.0 | 0.197 | 3.7 | 0.146 |
| LS-LED-V06S-16 | 16.0 | 0.630 | 5.0 | 0.197 | 3.7 | 0.146 |
| LS-LED-V06S-16A | 16.4 | 0.646 | 5.0 | 0.197 | 3.7 | 0.146 |
| LS-LED-V06S-17 | 17.0 | 0.669 | 5.6 | 0.220 | 3.9 | 0.154 |
| LS-LED-V06S-18B | 18.3 | 0.720 | 5.1 | 0.201 | 3.5 | 0.138 |
| LS-LED-V06S-19 | 19.0 | 0.748 | 5.0 | 0.197 | 3.9 | 0.154 |
| LS-LED-V06S-20 | 20.2 | 0.795 | 5.0 | 0.197 | 3.8 | 0.150 |
| LS-LED-V06S-22 | 22.0 | 0.866 | 5.1 | 0.201 | 3.9 | 0.154 |
| LS-LED-V06S-23 | 23.0 | 0.906 | 5.1 | 0.201 | 3.8 | 0.150 |

| | | | | | | |
|---|----------------------------|-----------------------|----------------------------|-------------------|---------------------------------|-------------------|
| DESCRIPTION NYLON LED SPACER | | | THIRD ANGLE PROJECTION | | Vaisis www.vaisis.com | |
| DWG DIMENSIONS UNLESS NOTED MM [INCH] | DWG. No. DW-LS-LED-V06S | PART No. SEE TABLE | DWN YW | DATE 4/13/2011 | CHKD YW | DATE 4/13/2011 |
| TOLERANCES UNLESS NOTED .X=±0.20 [0.008] .XX=±0.10 [0.004] FRAC=±1/64 ANG=1° | MATERIAL NYLON 66 | COLOR NATURAL | SCALE 4:1 | SHEET SIZE A | SHEET No. 1 OF 1 | |

| | | | |
|------|-----------------|-----------|----------|
| A | INITIAL RELEASE | 4/13/2011 | GC |
| REV. | DESCRIPTION | DATE | APPROVED |