



PART NO	HEIGHT "H"	
	MM	INCH
LS-LEDX-VL-3	3.0	0.118
LS-LEDX-VL-4	4.0	0.157
LS-LEDX-VL-5	5.0	0.197
LS-LEDX-VL-6	6.0	0.236
LS-LEDX-VL-7	7.0	0.276
LS-LEDX-VL-8	8.0	0.315
LS-LEDX-VL-9	9.0	0.354
LS-LEDX-VL-10	10.0	0.394
LS-LEDX-VL-11	11.0	0.433
LS-LEDX-VL-12	12.0	0.472

5MM(T1 3/4) LED

3MM(T1) LED




SAMPLE APPLICATION



NOTES:

- MAX LED SIZE: 5MM(T1 3/4)
- INTERLOCKABLE PARTS
- MATERIAL FLAMMABILITY RATING: UL94V-2
- COLOR AVAILABLE: NATURAL/BLACK
- CUSTOM MATERIAL AVAILABLE

DESCRIPTION				INTERLOCKING NYLON LED SUPPORT		 THIRD ANGLE PROJECTION		Vaisis www.vaisis.com	
DWG DIMENSIONS UNLESS NOTED				DWG. No.	PART No.	DWN	DATE	CHKD	DATE
MM [INCH]				DW-LS-LEDX-VL	SEE TABLE	YW	4/11/2011	YW	4/11/2011
A	INITIAL RELEASE	4/11/2011	GC	TOLERANCES UNLESS NOTED	MATERIAL	COLOR	SCALE	SHEET SIZE	SHEET No.
REV.	DESCRIPTION	DATE	APPROVED	.X=±0.20 [0.008] .XX=±0.10 [0.004] FRAC=±1/64 ANG=1°	NYLON 66	NATURAL	4:1	A	1 OF 1